

The *M*-Series

TM55 Telemount

Moffett *TM55* Telemount



Moffett **TM55** Telemount

TM55 Telemount

	TYPE	Telemount
1	CAPACITY @ 24" LOAD CENTER	5500 lbs
2	KUBOTA DIESEL ENGINE	60 hp
3	MAXIMUM REVS	3000 rpm
4	ELECTRICAL SYSTEM	12 Volt
5	DRIVE WHEELS	3
6	STEERING	Hydrostatic
7	FRONT TIRE TYPE (TREAD*) REAR TIRE TYPE (TREAD*)	31x15.5-15, 8-PLY (T.G.) 31x15.5-15, 8-PLY (T.G.)
8	TIRE OUTSIDE DIAMETER	31"
9	TIRE WIDTH	15 1/2"
10	MAXIMUM SPEED	7 mph
11	MAXIMUM GRADABILITY	30%
12	TURNING RADIUS	95"
13	UNLADEN WEIGHT	6100 lbs
14	WORKING PRESSURE FOR ATTACHMENTS	2500 psi
15	TILT OF MAST (FORWARD/BACK)	3°/5°
16	SIDESHIFT	4"
17	FORK SECTION	45x4x1 3/4"
18	REACH (BOOM STROKE)	52"
19	REACH (IN FRONT OF WHEELS — TRAILER BED HEIGHT)	39"
20	REACH (IN FRONT OF WHEELS — GROUND LEVEL)	26"
A	HEIGHT TO TOP OF CANOPY	94 1/2"
B	FORK CARRIAGE WIDTH (CLASS)	47" (III)
C	FRAME OPENING	59"
D	OVERALL WIDTH	101"
E	MINIMUM OVERHANG (Including Boom)	65 1/4"
F	WHEEL BASE	79"
G	C. OF G. FROM FORK FACE	18"
H1	LIFT HEIGHT	138"
H2	BOOM HEIGHT (RAISED)	168"
J	GROUND CLEARANCE	9 1/2"
K	FACE OF FORK TO CENTER OF FRONT TIRE (NOTE: "K" Changes depending on fork height)	20"
L	ANSI STANDARD	B56.6

The above specifications are not binding upon the manufacturer and may be changed without prior notice.
Weights may vary depending on tire and/or fork option. Weights are exclusive of (do not include) forks and attachments.



02/2007



more than a truck mounted forklift

Hiab, Inc.

12233 Williams Road
Perrysburg, Ohio 43551
Tel: 419.482.6000 Fax: 419.482.6001
Email: us.sales@hiab.com
www.hiabus.com



*T.G. = Tractor Grip | S.S. = Skid Steer | S.F. = Super Float